

244LD *Levelstar* Intelligent Buoyancy Transmitter for Liquid Level, Interface and Density with Torque tube – HART-Version –




The intelligent transmitter 244LD *LevelStar* is designed to perform continuous measurements for liquid level, interface or density of liquids in the process of all industrial applications. The measurement is based on the proven Archimedes buoyancy principle and thus extremely robust and durable. Measuring values can be transferred analog and digital. Digital communication facilitates complete operation and configuration via PC or control system. Despite extreme temperatures, high process pressure and corrosive liquids, the 244LD measures with consistent reliability and high precision. It is approved for installations in contact with explosive atmospheres. The 244LD *LevelStar* combines the abundant experience of FOXBORO ECKARDT with most advanced digital technology.


FEATURES

- HART Communication, 4 to 20 mA
- Configuration via FDT-DTM
- Multilingual full text graphic LCD
- IR communication as a standard
- Easy adaptation to the measuring point without calibration at the workshop
- Linear or customized characteristic
- 32 point linearisation for volumetric measurement
- Backdocumentation of measuring point
- Continuous self-diagnostics, Status and diagnostic messages
- Configurable safety value
- Local display in %, mA or physical units
- Process temperature from –196 °C to +500 °C
- Materials for use with aggressive media
- Micro sintermetal sensor technology

PACTware: Operation




Supply via power supply unit with communication; Ex




Furter supply circuits see Master Instruction document.


FDT-DTM: Configuration




Direct supply with communication; not Ex



CONNECTIONS, OPERATIONAL ELEMENTS



- 22** Cover for terminal compartment
- 24** Security lock for EEx d version
- 38** Cable gland (for cable Ø 6 to 12 mm)
- 39** Plug
- 50** Overvoltage protection (if present)



- 45** Terminal "+"
- 46** Terminal "-"
- 47** Ground terminal
- 48** External ground connection
- wire cross--
section up
to 2,5 mm²
- Test sockets Ø 2 mm integrated in terminals

TECHNICAL DATA

Data refer to the sensor material Type 316L (1.4404)

Explosion protection certificates must be observed!

Input / Output

Measuring ranges	50 mm to 50 m upper and lower range value continuously adjustable
Standard lenghts of Displacer (204DE)	350 .. 3000 mm, 14 .. 120 in; further lenghts on request
Weight of displacer ¹⁾	max. 25 N
Measuring span	2... 20 N contin. adjustable (to 1 N on request)
Span ratio	
Turn-down	1:1 .. 1:10 (1:20 on request)
Accuracy ²⁾	± 0.2 % ; increased accuracy with customized adjustment
Transfer function	linear or customized with up to 32 setpoints

Configuration

- with FDT-DTM per HART protocol
 - via 2-wire connection 4 .. 20 mA
 - via IR communication
 - with multi-lingual, full graphic LCD display with %, mA,
physical units and 2 from the outside-to-use buttons
- Load $R_{B\max} = (U_s - 12 \text{ V}) / 23 \text{ mA}$

Communication HART

Connection	Two-wire system
Supply voltage U_s ³⁾	>12 V + $R_b * 0.025 \text{ A}$
R_b is the total burden resistor for lines, HART measure- ment resistor and communication.	
Current sink	max. 24 mA
Signal range	4 to 20 mA
Operating range	3.8 to 20.5 mA (acc. NE43)

Critical error alarms in the 2-wire

Communication < 3.6 mA and > 21 mA

HART Protocol

- 2-wire 1200 Baud, HART compliant
- IR communication 19200 Baud

Communication Hardware

- Handterminal HT 375/475
- PC Software WINxx and FDT/DTM

Operating conditions ⁴⁾

Process temperature -196 °C ... +500 °C

Pressure rating

- acc. to DIN PN 16, 40, 63, 100, 160, 250
- acc. to ANSI Class 150, 300, 600, 900, 1500

Ambient temperature ^{5) 6)} -40 °C ... +70 °C ⁷⁾

Relative humidity up to 100 %

Condensation permitted

Transportation-

storage temperature -40 °C ... +85 °C

Protection IP 66 (acc. DIN 40 050)

The device can be operated at a class D2 location in
accordance with DIN IEC 654, part 1.

Operation condition effects

Ambient temperature -10 °C ... +70 °C

Zero < 0.1 % / 10 K ⁸⁾

Span < 0.07 % / 10 K

Total

$$(0.1 \frac{\text{max. sp.}}{\text{adjusted sp.}} \pm 0.07 \frac{\text{measured value}}{\text{adjusted sp.}}) \% / 10 \text{K}$$

(sp. = measuring span)

< -10 °C / > +70 °C twice the value

Process temperature < 0.1 % / 10 K ⁸⁾

Operating pressure no influence (vakuum resis-
tant)

Transitional behavior

Dynamic behavior

Damping (90%-time) 0 ... 32 s

Switch-on time 7 s

Step response (63%-time)

with damping 0 s 250 ms

Update rate 10/s

Long term stability < 0.2 % / 6 months at 20°C ⁸⁾

Noise suppression

Common mode voltage < AC 250 V_{eff}

Common mode rejection 120 dB

Series mode rejection 50 dB

Filter Smart Smoothing

1) For measurement of interface or density:

weight 25 N + buoyant force at lowest density

2) Accuracy acc. ANSI / ISA - S51.1 - 1979

3) Us (max) with explosionproof device < 30 V, otherwise < 42 V

4) Not with all materials – see Table of Comparison of Materials page 6

5) Ambient temperature must not exceed 50 °C at measuring module
housing, when process medium or heating of medium exceed 300 °C

6) -50 °C on request

7) Display not readable at T < -20 °C or T > +70 °C

8) For max. measuring span

Material, Pressure Rating & Contact Face, Mounting Direction

see Model Codes

Material Amplifier housing . . . Aluminum
(Alloy No. GD-Al Si 12),
Polyurethan coated
or Stainless Steel

For Sour Gas applications acc. to NACE Standard MR-0175-95:
Wafer body 316L (1.4404)
Torque tube Hastelloy C or Inconel 600

The material of the seal at the Torque tube bearing corresponds to the material of the head piece.

Mounting

Mounting method sandwich mounted
acc. to DIN DN 80, DN 100
acc. to ANSI 3 inch, 4 inch

Note: Always follow the RH or LH version! See the picture below. The device can not be used "upside down". All internal parts are mounted and calibrated in inverse manner. The conversion can be performed only by the manufacturer or a contractual partner. Otherwise calibration and pressure test are invalid.

Weight

Transmitter see table page 7
Displacer see table page 10

Electrical connection

Cable entry thread M20x1.5 or 1/2-14 NPT
Cable gland and screwed sealing plug have to be ordered separately under model code BUSG ...

For equipment in Ex d version, 1 screwed sealing plug made of stainless steel is included in delivery.
Screw terminals wire cross-section up to 2.5 mm²
Test sockets Ø 2 mm

Electromagnetic compatibility EMC

Operating conditions industrial environment
Immunity according to

EN 61326 (3/2002) fulfilled

Emission according to

EN 61326 (3/2002) fulfilled

EN 55011, May 2000,

Group 1, Class A. fulfilled

EN 50081-2. fulfilled

NAMUR recommendation Ne21 Status Aug.1998 fulfilled

SAFETY REQUIREMENTS

CE Label

Electromagnetic
compatibility 2004/108/EC fulfilled
Explosion protection acc. to ATEX . . . 94/9/EC

Safety


According to EN 61010-1

(resp. IEC 1010-1) safety class III

Internal fuses none (or not replaceable by customer)

External fuses Limitation of power supplies
for fire protection have to be observed due to EN 61010-1,
appendix F (rsp. IEC 1010-1)

244LD LevelStar versions ...



Electrical classification ATEX^{2) 3)}

intrinsic safe:

AID 421	II 1/2 G EEx d ib/ia IIC/IIB T4/T6	PTB 04 ATEX 2011X	Zone 0
AID 421	II 2 G EEx d ib/ia IIC/IIB T4/T6	PTB 04 ATEX 2011X	Zone 1

explosion-proof:

AD 432	II 1/2 G Ex da/db IIB/IIC T4/T6	PTB 02 ATEX 1025 X	Zone 0
AD 432	II 2 G Ex da/db IIB/IIC T4/T6	PTB 02 ATEX 1025 X	Zone 1

Zone 2:

Manufacturer's Declaration


Further certificates see also our website:

http://www.foxboro-eckardt.eu/Ex_de_en/allEX_244LD_en_de.html


- FM
- CSA
- NEPSI
- Russia
- Kasachstan
- Approvals for use on sea ships

Version with heating jacket;
sandwich-mounted between displacer
chamber 204DC and cover flange 204BCF,
with displacer 204DE

204BCF



204DE



2) With appropriate order only

3) National requirements have to be observed

Comparison of Material

Code	WNr	DIN	Remarks	equivalent to
St 35.8 III	1.0305 1.0345	EN 10 216-2		ASTM A 106 Gr.8
C 22.8	1.0460	EN 10 273	VdTÜV - Wbl. 350/3	ASTM A 105 ~ ASTM Typ 316Ti
X6 CrNiMoTi 17 12 2	1.4571	17 440		ASTM Typ 316L
X2 CrNiMo 17 13 2	1.4404			
X2 CrNiMo 18 14 3	1.4435			
X5 CrNiMo 17 13 3	1.4436			
NiMo 16 Cr 15 W	2.4819	17 744	equ. to Hastelloy C-276 VdTÜV - Wbl. 400	UNS N 12 276
NiCr 15 Fe	2.4816	17 742	Inconel 600 VdTÜV - Wbl. 305	UNS N 06600
NiCr 22 Mo 9 Nb	2.4856	17 744	Inconel 625 VdTÜV 499	UNS N 06625
NiCr 21 Mo	2.4858	17 744	Inconel 825 VdTÜV 432	UNS N 08825
X 2 CrNiMo 22 5 3	1.4462	EN 10222-5	Duplex	UNS 31803
GD - AISI 12	3.2582.05	17 007	Al - Diecasting	

Service Limits of wafer body PN 250 made of (material)

Max. operating pressure in bar at temperature in °C

1.0460

°C	-10 ... +120	200	250	300	350		
bar	250	200	175	150	140	DIN	
bar	231	219	206	180	145	ANSI	

1.4404 / 1.4435 / 1.4571

°C	-196 ... -10	-10 ... +50	100	200	300	400	500	
bar	250	250	230	200	177	162	148	DIN
bar	248	248	211	178	158	145	138	ANSI

1.4462

°C	-40 ... +50	100	150	200	250	280	
bar	250	225	209	194	184	178	DIN
bar	260	234	218	201	191	185	ANSI

Inconel 625¹⁾

°C	-10 ... +50	100	200	300	400	450	
bar	250						DIN
bar	260	1)					ANSI

Inconel 825

°C	-10 ... +50	100	200	300	400	450	
bar	250	216	187	176	164	158	DIN
bar	260	224	195	183	171	165	ANSI

HC

°C	-196 ... -10	50	100	200	300	400	
bar	250	250	233	209	200	184	DIN
bar	260	260	243	217	209	192	ANSI

Table of Weights

Transmitter	Weight [kg]					
	DIN PN		ANSI Class			
	16 ... 160	250	150	300 / 600	900	1500
DN 80 / 3 inch	12.5		12.5		12.5	
DN 100 / 4 inch	13.5		13.5		13.5	

1) Values on request

MODEL CODES 244LD *LevelStar*

Intelligent Buoyancy Transmitter with Torque Tube		244LD	010812
Wafer Body Material (Process wetted):			
Carbon Steel 1.0460 (~A 105), application from -10°C to +350°C	-K		
1.4404 equivalent to 316L / 1.4435, application from -60°C to +400°C (material is 1.4435 when Wafer Body Pressure Rating codes H1and H2 selected) . . . -S			
1.4404 equivalent to 316L / 1.4435, application from -196°C to +400°C (material is 1.4435 when Wafer Body Pressure Rating codes H1and H2 selected) . . . -U			
1.4404 equivalent to 316L / 1.4435, application from -60°C to +500°C (material is 1.4435 when Wafer Body Pressure Rating codes H1and H2 selected) . . . -T			
Duplex - 1.4462, application from -10°C to +280°C (no PED Certification)	-N		
Inconel 625 - 2.4856, application from -10°C to +450°C (no PED Certification)	-A		
Inconel 825 - 2.4858, application from -10°C to +450°C (no PED Certification) (p)	-I		
Hastelloy C , application from -196°C to +400°C.	-C		
Torque Tube Material (Process wetted):			
1.4404 equivalent to 316L	S		
Hastelloy C	C		
Inconel 600 - 2.4816.	I		
Monel K500- 2.4375	M		
Wafer Body Flange Size (Nominal size):			
DN70 (available with Wafer Body Material S, U, T and Torque Tube Material S and C)	0		
DN80.	1		
DN100.	2		
3-Inch	3		
4-Inch	4		
Wafer Body Pressure Rating & Contact Face			
PN40 (PN16 to PN40) B1/B1 (Contact Face DIN EN 1092-1) . (a)	B1		
PN250 (PN16 to PN250) B2/B2 (Contact Face DIN EN 1092-1) (Draft DIN EN 1092-1:2005-04) (a)	B2		
PN250 (PN16 to PN250) D/C (Contact Face DIN EN 1092-1) (Draft DIN EN 1092-1:2005-04) (a)(r)	DC		
PN250 (PN16 to PN250) D/D (Contact Face DIN EN 1092-1) (Draft DIN EN 1092-1:2005-04) (a)	DD		
PN250 (PN16 to PN250) F/F (Contact Face DIN EN 1092-1) (Draft DIN EN 1092-1:2005-04) (a)	FF		
PN250 (PN16 to PN250) F/E (Contact Face DIN EN 1092-1) (Draft DIN EN 1092-1:2005-04) (a)(s)	FE		
PN250 (PN16 to PN250) L/L (Contact Face DIN 2696) (a)	L1		
PN400 L/L Lense (Contact Face DIN 2696) (k) (n)	H1		
PN500 L/L Lense (IG-Norm High Pressure Version) (i) (n)	H2		
ANSI Class 150 RF/RF	(b)	R1	
ANSI Class 900 (300/600/900) RF/RF	(b)	R2	
ANSI Class 1500 RF/RF	(b)	R3	
ANSI Class 150 SF/SF.	(b)	S1	
ANSI Class 900 (300/600/900) SF/SF	(b)	S2	
ANSI Class 1500 SF/SF	(b)	S3	
ANSI Class 150 RJF/RJF	(b)	J1	
ANSI Class 900 (300/600/900) RJF/RJF	(b)	J2	
ANSI Class 1500 RJF/RJF.	(b)	J3	
ANSI Class 300 to 1500, Form LF/LM	(b)	LM	
ANSI Class 300 to 1500, Form LF/LF.	(b)	LF	
ANSI Class 300 to 1500, Form LG/LT.	(b)	LT	
ANSI Class 300 to 1500, Form LG/LG	(b)	LG	

MODEL CODES 244LD *LevelStar* (continued)

(Wafer Body Pressure Rating & Contact Face)									
ANSI Class 150, Form SG/ST	(b)	GT							
ANSI Class 300 to 1500, Form SG/ST	(b)	ST							
ANSI Class 150, Form SG/SG	(b)	GG							
ANSI Class 300 to 1500, Form SG/SG	(b)	SG							
Wafer Body Mounting Direction: (Amplifier to body)									
Right Hand mounted		R							
Right Hand mounted with heating jacket -									
- connecting flanges B1 / DN15, PN40 (DIN EN 1092-1)	(m)(o)(z)	A							
- connecting flanges B1 / DN25, PN40 (DIN EN 1092-1)	(m)(o)(z)	B							
- connecting flanges B2 / DN15, PN40 (DIN EN 1092-1)	(m)(o)(z)	C							
- connecting flanges B2 / DN25, PN40 (DIN EN 1092-1)	(m)(o)(z)	D							
- connecting flanges RF/SF, 1/2 in, Class 300	(m)(o)(z)	E							
- connecting flanges RF/SF, 1 in, Class 300	(m)(o)(z)	F							
- connecting flanges RJF, 1/2 in, Class 300	(m)(o)(z)	G							
- connecting flanges RJF, 1 in, Class 300	(m)(o)(z)	H							
Left Hand mounted		L							
Left Hand mounted with heating jacket -									
- connecting flanges B1 / DN15, PN40 (DIN EN 1092-1)	(m)(o)(z)	M							
- connecting flanges B1 / DN25, PN40 (DIN EN 1092-1)	(m)(o)(z)	N							
- connecting flanges B2 / DN15, PN40 (DIN EN 1092-1)	(m)(o)(z)	O							
- connecting flanges B2 / DN25, PN40 (DIN EN 1092-1)	(m)(o)(z)	P							
- connecting flanges RF/SF, 1/2 in, Class 300	(m)(o)(z)	S							
- connecting flanges RF/SF, 1 in, Class 300	(m)(o)(z)	T							
- connecting flanges RJF, 1/2 in, Class 300	(m)(o)(z)	U							
- connecting flanges RJF, 1 in, Class 300	(m)(o)(z)	V							
Version:									
Base VERSION - TRANSSTAR- (244LD)		B							
Base VERSION - LEVELSTAR- (244LD)	(f)(v)	N							
Base (B) + Displacer (244LD + 204DE)		S							
Base (N) + Displacer (244LD + 204DE)	(f)(v)	T							
Base (B) + Displacer + Displacer Camber + Flange combination + Flange (244LD + 204DE + 204DC + 204FK + 204BCF)	(h)	C							
Base (N) + Displacer + Displacer Camber + Flange combination + Flange (244LD + 204DE + 204DC + 204FK + 204BCF)	(f)(v)(h)	D							
Cable Entry:									
M20x1.5 without cable gland		M							
1/2-14 NPT without cable gland		N							
Communication:									
HART		H							
PROFIBUS-PA		P							
FOUNDATION Fieldbus H1		B							
Electrical Classification:									
ATEX intrinsic safe Zone 0, IIC T4 (HART)	(d)	0C4							
ATEX Intrinsic safe Zone 0, IIC T6 (HART, PROFIBUS or FOUNDATION Fieldbus)	(d)	0C6							
ATEX intrinsic safe Zone 1, IIC T4 (HART)		1C4							
ATEX intrinsic safe Zone 1, IIC T6 (HART, PROFIBUS or FOUNDATION Fieldbus)		1C6							
ATEX intrinsic safe Zone 2, IIC T4 (HART)		2C4							
ATEX intrinsic safe Zone 2, IIC T6 (PROFIBUS or FOUNDATION Fieldbus) Zone 2, IIC T6 (HART) VERSION N, T, D	(c)	2C6							
ATEX explosionproof Zone 0, IIC T6	(d)	D0C							
ATEX explosionproof Zone 1, IIC T6		D1C							
FM Nonincendive (HART) (PROFIBUS or FOUNDATION Fieldbus)	(c)	NFM							
FM Explosionproof		FDZ							
CSA Explosionproof		CDZ							
FM Intrinsically Safe (HART) (PROFIBUS or FOUNDATION Fieldbus)	(c)	FAA							
CSA Intrinsically Safe	(c)	CAA							

(continued on next page)

MODEL CODES 244LD *LevelStar* (continued)

(Electrical Classification)			
GOST-R Intrinsically Safe, T4 (HART)	GA4		
GOST-R Intrinsically Safe, T6 (HART, PROFIBUS or FOUNDATION Fieldbus)	GA6		
GOST-R Explosionproof, T6	GDZ		
NEPSI Intrinsically Safe, T4 (HART)	NA4		
NEPSI Intrinsically Safe, T6 (HART, PROFIBUS or FOUNDATION Fieldbus)	NA6		
NEPSI Explosionproof, Ex d IIC T4-T6	NDZ		
For General Purpose Areas; not Explosionproof	ZZZ		
OPTIONS:			
Housing Complete Stainless Steel without external Pushbuttons (not available with Wafer Body Material codes K)	-H		
External Pushbuttons for Maintenance	(n)		-M
Remote Amplifier Mounting Kit (3 m), Mounted	(e)(u)		-R
Remote Amplifier Mounting Kit (10m), Mounted	(e)(u)		-B
Tag No. Labeling			
Stainless Steel Label Fixed With Wire			-L
Stainless Steel Label Fixed On Amplifier			-F
National Certificates			
TA-Luft	(u)		-K
ABSA (Canada)	(u)		-A
Germanischer Lloyd	(q)(u)		-G
Certificates			
EN 10204-2.1 , Certificate Of Compliance			-1
EN 10204-2.2 , Specific Test Report (Calibration)			-2
EN 10204-3.1 , Inspection Certificate Of Process Wetted Material			-3
PED 97/23/EC additional unit verification, acc. to module F/G (Not available with Wafer Body Material codes N and I)			-4
Comply With NACE Standard MR-0175 (available with Torque Tube Material I, M or C)	(g)		-6
SIL 2 Certificate	(q)		-Q
Material Test			
X-Ray And Isotope Test For Weldings			-7
Dye Penetration Test			-8
PMI - Test			-5
Subassemblies			
Torque Tube for selected code (244LD-*****-W)	(p)		-W
Amplifier for selected code (244LD-*****-X)	(p)		-X
Complete Sensor for selected code (244LD-*****-Y)	(p)		-Y
Wafer body for selected code (244LD-*****-Z)	(p)		-Z
(a) Available with Wafer Body Flange Size 1 or 2			
(b) Available with Wafer Body Flange Size 3 or 4			
(c) Pending			
(d) Not available with Wafer Body Pressure Rating & Contact Face codes L1, J1, J2, J3, H1, H2, DD			
(e) Not available with Electrical Classification FDZ, CDZ, 0C6, D0C, D1C, GDZ, NDZ or Optional Features -H			
(f) only with Communication H (HART) and electrical Classification 0C6, 1C6, D0C, D1C, 2C6			
(g) Restrictions concerning the limit of application for the used materials are to considering (NACE Standard MR-0175/2003, bzw. ISO 15156-3)			
(h) Pending, order separately at this time.			
(i) Available with Wafer Body Flange Size 0			
(k) Available with Wafer Body Flange Size 1			
(m) Not available with Wafer Body Flange Size code 4 with Wafer Body Pressure Rating code J3			
(n) Not available with Wafer Body Material codes A, K,N, I, C or Torque Tube Material codes I and M			
(o) Not available with Wafer Body Material codes A, K, U, N, I, C			
(p) on request			
(q) Available with HART			
(r) D at top			
(s) F at top			
(u) Not applicable with Version N, T, D			
(v) Pending Electrical Classsification FDZ, CDZ, GA6, GDZ, NA6, NDZ, BA6, BDZ			
(w) Version N, T, D with external Pusbuttons			
(x) available with version N, T, D			
(y) Not with Optionals -H and Version B, S or C			
(z) Not with Pressure Rating H1 or H2			

Displacer 204DE

Typical Dimensions and Weights for Density Ranges $\Delta \rho$ ¹⁾

Material	316L (1.4404 / 1.4435) ²⁾												PTFE / PTFE with 25 % C			Hastelloy C								
	Code				-S (PN 100)				-T ³⁾ (PN 40 / 63)				-S (PN 250)				-S (PN 500)							
Len. L	Density Range $\Delta \rho$																							
	250 ... 1500 kg/m ³				100 ... 600 kg/m ³				400 ... 2000 kg/m ³				200 ... 1500 kg/m ³				300 ... 1500 kg/m ³							
Ø mm	Vol. cm ³	Wei. N	PN bar	Ø mm	Vol. cm ³	Wei. N	PN bar	$\rho_{min}^{4)}$ kg/m ³	Ø mm	Vol. cm ³	Wei. N	PN bar	Ø mm	Vol. cm ³	Wei. N	PN bar	Ø mm	Vol. cm ³	Wei. N	PN bar				
350	60,3	1000	19	100	101,6	2840	38	40	460	42,4	500	18	250	62	1056	23	500	60,3	1000	18	100			
500	48,3	920	17	100	88,9	3100	43	63	580	42,4	710	24	250	51	1021	23	500	48,3	920	19	100			
750	42,4	1060	21	100	76,1	3410	44	63	545	33,7	670	21	250	42	1039	24	500	48,3	1370	27	100			
1000	33,7	890	17	100	60,3	2855	41	63	545	26,9	570	18	250	35	961	21	500	33,7	890	19	100			
1200	33,7	1070	20	100	60,3	3425	48	63	675	26,9	680	22	250	35	1153	25	500	33,7	1070	22	100			
1500	26,9	850	16	100	51	3065	39	63	460	21,3	540	17	250	30	1060	24	500	26,9	850	18	160			
1800	26,9	1020	19	100	42,4	2540	38	63	495	21,3	640	20	250	28	1107	25	500	26,9	1020	21	160			
2000	26,9	1140	21	100	42,4	2825	41	63	565	21,3	710	22	250	25	981	22	500	26,9	1140	23	160			
2500	21,3	890	20	100	38	2840	37	63	425	17,2	580	16	250	22,5	993	23	500	21,3	890	23	160			
3000	21,3	1070	24	100	38	3400	45	63	575	17,2	700	23	250	20	942	22	500	21,3	1070	27	160			
inch																								
14	60,3	1020	20	100	101,6	2885	38	40	455	42,4	510	18	250	62	1074	23	500	60,3	1020	18	100			
32	42,4	1150	23	100	76,1	3700	47	63	595	33,7	730	23	250	42	1126	26	500	33,7	720	16	100			
48	33,7	1090	20	100	60,3	3480	49	63	680	26,9	690	22	250	35	1171	26	500	33,7	1090	23	100			
60	26,9	870	16	100	51	3115	40	63	465	21,3	540	18	250	30	1076	24	500	26,9	870	18	100			
72	26,9	1040	19	100	42,4	2580	38	63	505	21,3	650	21	250	28	1124	26	500	26,9	1040	21	160			
84	26,9	1210	22	100	42,4	3000	44	63	635	21,3	760	23	250	25	1046	24	500	26,9	1210	25	160			
96	21,3	870	20	100	38	2765	37	63	420	17,2	570	16	250	22,5	968	22	500	21,3	870	23	160			
120	21,3	1090	25	100	38	3455	46	63	595	17,2	710	24	250	20	957	22	500	21,3	1090	25	160			

1) $\Delta \rho = \rho_1 - \rho_2$

ρ_1 = density of lower medium

ρ_2 = density of upper medium


- 2) Using displacer material 1.4571 can cause small deviations in diameter, volume and weight.
- 3) For measurement of interface or density, the max. density of the lower medium is 1350 kg/m³.
- 4) Min. density of the lower medium

If a Displacer Chamber is used, the difference between the diameter of the Displacer and the inside diameter of the Displacer Chamber must be at least 10 mm.

Lengths < 350 mm and > 3000 mm, and density ranges < 100 kg/m³ and > 2000 kg/m³ on request.

Accessories

For Displacer Chamber 204DC, Flange combination 204FK and Cover Flange Kit 204BCF see PSS EML0901, 204.. Accessories for Buoyancy Transmitter.



MODEL CODES 204DE**Displacer for Buoyancy Transmitters from 2N buoyancy up to 20N 204DE**

010210

RANGE OF APPLICATION: (a)

Liquid Level - Media: Liquid / Gas or Air
 (Density difference = 250 kg/m³ to 2000 kg/m³)
 (= 9x10⁻³ lbm/in³ to 72.2x10⁻³ lbm/in³) -S

Interface Level / Density - Media: Liquid 1 / Liquid 2
 (Density difference = 100 kg/m³ to 600 kg/m³)
 (= 3.6x10⁻³ lbm/in³ to 22.7x10⁻³ lbm/in³) -T

DISPLACER MATERIAL:

316L (1.4404 / 1.4435 / 1.4571)	S
PTFE (not for applications in Zone 0)	P
PTFE With 25% Carbon	O
Hastelloy C	C
Inconel 625 (2.4856)	I
Monel 400 (2.4360)	M
Titan (3.7035)	T

PRESSURE RATING:

Up to PN 100 / Class 600	D
Up to PN 160 / Class 900	E
Up to PN 250 / Class 1500	F
Up to PN 500 / Class 2500	G

SUITABLE FOR FLANGE SIZE: (at Top of vessel/chamber)

DN 50	0
DN 70	1
DN 80	2
DN 100	3
DN 150	4
2 inch	5
3 inch	6
4 inch	7
6 inch	8

DISPLACER LENGTH "L": (inches are approx.)

for Displacer Material codes P and O:

300 mm (12 in) to 2000 mm (79 in) without partitioning	A
2001 mm (79 in) to 4000 mm (157 in) One partition point	B
4001 mm (157 in) to 6000 mm (236 in) Two partition points	C
6001 mm (236 in) to 8000 mm (315 in) Three partition points	D
8001 mm (315 in) to 10000 mm (394 in) Four partition points	E
10001 mm (394 in) to 12000 mm (472 in) Five partition points	F

for Displacer Material S, C, I, M and T:

300 mm (12 in) to 3000 mm (118 in) without partitioning	K
3001 mm (118 in) to 6000 mm (236 in) One partition point	L
6001 mm (236 in) to 9000 mm (354 in) Two partition points	M
9001 mm (354 in) to 12000 mm (472 in) Three partition points	N
12001 mm (472 in) to 15000 mm (591 in) Four partition points	O

MATERIAL AND LENGTH OF THE SUSPENSION: (Length "b") (d)

316L / 1.4404 / ... Standard length of Suspension . . . (b)	S1
316L / 1.4404 / ... Customized Suspension-Length . . . (c)	S2
Hastelloy C Standard length of Suspension . . . (b)	C1
Hastelloy C Customized Suspension-Length . . . (c)	C2
Inconel Standard length of Suspension . . . (b)	I1
Inconel Customized Suspension-Length . . . (c)	I2
Monel Standard length of Suspension . . . (b)	M1
Monel Customized Suspension-Length . . . (c)	M2
Titan Standard length of Suspension . . . (b)	T1
Titan Customized Suspension-Length . . . (c)	T2

(continued on next page)

MODEL CODES 204DE (continued)**OPTIONS:**

for application in Zone 0 (Additional grounding rope) (not available with Displacer Material: P)	-E
Damping Spring (Mat. 1.4310, Max. 250°C (482F)) (f)	-D
Damping Spring (Mat. HC, Max 350°C (662F)) (f)	-C
Degreased	-O
Tag No. Labeling Stainless Steel Label Fixed With Wire (Text required)	-L

Certificates

EN 10204-2.1 Certificate Of Compliance	-1
EN 10204-3.1 Inspection Certificate Of Process Wetted Material (not available with Displacer Material: P and O)	-3
PMI - Test (not available with Displacer Material: P and O)	-5

Footnotes

- (a) Upper and Lower Medium Density required (at operating temperature)
- (b) Only in connection with Modelcode 204DC
- (c) Exact length required (Contact face of flange to upper end of displacer)
- (d) All +/- 8mm (0.3 inch)
- (e) Pending
- (f) Required for 244LD Version B with Option -G

Table of versions for dimensions c, d, g see drawing on next page

Version		Form of Sealings	DN 80 / 3 inch			DN 100 / 4 inch						
PN	c		d	g	c	d	g					
DIN EN	16	B1 DIN EN 1092	B2 / C / D / F / E DIN EN 1092	140	82	140	160	102				
	40											
	63	Form L DIN 2696					162					
	100											
	160											
	250											
ANSI	150	RF / SG / ST ANSI B16.5	140	82	140	160	102	162				
	300											
	600											
	900											
	1500											
	150	RJF ANSI B16.5				140	102	174				
	300											
	600											
	900											
	1500											
	300	LF / LM / LG / LT ANSI B16.5				160	102	206				
	600											
	900											
	1500											

RF Raised Face

RJF Ring Joint Face

LF Large Female

LM Large Male

LG Large Groove


LT Large Tongue

SG Small Groove

ST Small Tongue

DIMENSIONS

244LD up to PN 250 / Class 1500



Product Specifications for Intelligent Transmitters

Product Specification: Device:

PSS EML0610	<u>144LD</u>	Intelligent Buoyancy Transmitter for Liquid Level, Interface and Density with Displacer and Torque Tube
PSS EML0710 A	<u>244LD</u>	Intelligent Buoyancy Transmitter for Liquid Level, Interface and Density with Displacer and Torque Tube (A: <i>TransStar</i> G: <i>LevelStar</i>)
PSS EML0710 G		
PSS EML1610	<u>144LVD</u>	Intelligent Buoyancy Transmitter for Liquid Level, Interface and Density with Displacer
PSS EML1710	<u>244LVP</u>	Intelligent Buoyancy Transmitter for Liquid Level, Interface and Density with Displacer
PSS EML0901	<u>204xx</u>	Accessories for Buoyancy Transmitters
PSS EMO0100		Accessories for Devices with HART-Protocol

Subject to alterations - reprinting, copying and translation prohibited. Products and publications are normally quoted here without reference to existing patents, registered utility models or trademarks. The lack of any such reference does not justify the assumption that a product or symbol is free.

FOXBORO ECKARDT GmbH
Pragstr. 82
D-70376 Stuttgart
Tel. +49 (0)711 502-0
Fax +49 (0)711 502-597
Mail to: salessupport@foxboro-eckardt.de
<http://www.foxboro-eckardt.eu>



DOKT 556 588 038~1

i n v e n s y s
Operations Management